

## Clean Copy of the Current Claims as Amended

Claim 1 (Canceled)

Claim 2 (Canceled)

Claim 3 (Canceled)

Claim 4. (Currently amended) A device for work piece milling on a woodworking tool having a cutting portion, the woodworking tool chosen from the group consisting of a wood shaper, a router table and a table saw, the woodworking tool allowing work piece movement on the woodworking tool through the cutting portion in a first direction, the device comprising:

a. an indexing system comprising:

1) an indexing channel system including at least one channel having an elongated slot, the channel having a channel stop securable at one end of the elongated slot, the channel being attachable to the woodworking tool so that the channel is secured to the woodworking tool so that the elongated slot is approximately perpendicular to the direction of work piece movement through the cutting portion on the woodworking tool;

2) at least one indexing spacer of predeterminable length that fits within and is retained in the elongated slot of the channel; and

b. a horizontal plate attachable to the indexing system through at least one adjustable connection, the connection having a connection member extending into the elongated slot of the channel, the connection member interacting with the elongated slot to secure the horizontal plate to the channel in a spaced relationship from the channel stop, the spaced relationship determined by the length of the indexing spacer;

whereby, once the indexing channel system is secured to the woodworking tool and the channel stop securely located at the one end of the elongated slot, the horizontal plate is moved toward the cutting portion until the connection member contacts the indexing spacer so that the horizontal plate is positioned a distance from the cutting portion of the woodworking tool in a precisely determined distance from the cutting portion of the woodworking tool, the distance determined by the length of the indexing spacer.

Claim 5 (Canceled)

Claim 6 (Canceled)

Claim 7 (Canceled)

Claim 8 (Canceled)

Claim 9 (Canceled)

Claim 10 (Canceled)

Claim 11. (Previously presented) The device of claim 4 further comprising a bracket interlocking the device to a fence system.

Claim 12. (Canceled)

Claim 13. (Currently amended) The device of claim 4 wherein: the channel of the indexing channel system is an extruded piece; the elongated slot is formed in cross-section in an upright or inverted T shape; and the connection includes anchoring means interacting with the elongated slot for securing the horizontal plate to the indexing channel system.

Claim 14. (Previously presented) The device of claim 4 wherein the indexing spacer of predeterminable length is chosen from a group consisting of indexing spacers having a preset length or an adjustable length.

Claim 15 (Canceled)

Claim 16. (Previously presented) The device of claim 14 wherein the indexing spacer of predeterminable length comprises a body having a threaded hole and an opposed end and a hex bolt having a head, the hex bolt having threads that are threaded into the threaded hole of the body whereby the distance from the opposed end of the body and the head of the hex bolt, and consequently the length of the spacer, is determined by rotating the hex bolt into or out of the threaded hole of the body.

Claim 17. (Previously presented) The device of claim 14 wherein the indexing spacer of predeterminable length comprises:

- at least two finger gauges aligned side by side, each finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- a connecting bolt extending through the holes in the finger gauges, the connecting bolt holding the gauges in side by side alignment.

Claim 18. (Previously presented) The device of claim 14 wherein the indexing spacer of predeterminable length comprises:

- at least three relatively thick finger gauges aligned side by side, each relatively thick finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- at least three relatively thin finger gauges aligned side by side, each relatively thin finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- a first connecting bolt extending through the holes in the finger gauges, the first connecting bolt holding the gauges in side by side alignment.

Claim 19. (Previously presented) The device of claim 18 wherein each of the at least three relatively thin finger gauges are each one third the thickness of one of the relatively thick finger gauges.

Claim 20. (Previously presented) The device of claim 18 further comprising:  
a second connecting bolt;  
a pair of plates located on opposed sides of the finger gauges, the pair of plates attached to and pivoting about the first connecting bolt, the pair of plates having holes at one end to allow the second connecting bolt to pass therethrough; and  
a block located between the pair of plates at one end of the finger gauges, the block having a hole extending entirely through the block, the hole in the block holding the second connecting bolt whereby the block pivots about the second connecting bolt.

Claim 21. (Currently amended) A device for work piece milling on a woodworking tool having a cutting portion, the woodworking tool chosen from the group consisting of a wood shaper, a router table and a table saw, the woodworking tool allowing work piece movement on the woodworking tool through the cutting portion in a first direction, the device comprising:

- a. an indexing system comprising:
  - 1) an indexing channel system including at least one channel having an elongated slot, the channel having a channel stop securable at one end of the elongated slot, the channel being attachable to the woodworking tool so that the channel is secured to the woodworking tool so that the elongated slot is approximately perpendicular to the direction of work piece movement through the cutting portion on the woodworking tool wherein: and
    - the channel of the indexing channel system is an extruded piece;
    - the elongated slot is formed in cross-section in an upright or inverted T shape;
  - 2) at least one indexing spacer of predeterminable length that fits within and is retained in the elongated slot of the channel wherein the indexing spacer of predeterminable length may either have a preset length or an adjustable length; and
- b. a horizontal plate attachable to the indexing system through at least one adjustable connection, the connection having a connection member extending into the elongated slot of the channel, the connection member interacting with the elongated slot to secure the horizontal plate to the channel in a spaced relationship from the channel stop, the spaced relationship determined by the length of the indexing spacer;  
whereby, once the indexing channel system is secured to the woodworking tool and the channel stop securely located at the one end of the elongated slot, the horizontal plate is moved toward the cutting portion until the connection member contacts the indexing spacer so that the horizontal plate is positioned a distance from the cutting portion of the woodworking tool in a precisely determined distance from the cutting portion of the woodworking tool, the distance determined by the length of the indexing spacer.

**Claim 22.** (Previously presented) The device of claim 21 further comprising a bracket interlocking the device to a fence system.

**Claim 23.** (Previously presented) The device of claim 21 wherein the indexing spacer of predeterminable length comprises a body having a threaded hole and an opposed end and a hex bolt having a head, the hex bolt having threads that are threaded into the threaded hole of the body whereby the distance from the opposed end of the body and the head of the hex bolt, and consequently the length of the indexing spacer, is determined by rotating the hex bolt into or out of the threaded hole of the body.

**Claim 24.** (Previously presented) The device of claim 21 wherein the indexing spacer of predeterminable length comprises:

- at least two finger gauges aligned side by side, each finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- a connecting bolt extending through the holes in the finger gauges, the connecting bolt holding the gauges in side by side alignment.

**Claim 25.** (Previously presented) The device of claim 21 wherein the indexing spacer of predeterminable length comprises:

- at least three relatively thick finger gauges aligned side by side, each relatively thick finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- at least three relatively thin finger gauges aligned side by side, each relatively thin finger gauge having a hole extending entirely through the finger gauge transverse to the side by side alignment;
- a first connecting bolt extending through the holes in the finger gauges, the first connecting bolt holding the gauges in side by side alignment.

**Claim 26.** (Previously presented) The device of claim 25 wherein each of the at least three relatively thin finger gauges are each one third the thickness of one of the relatively thick finger gauges.

**Claim 27.** (Previously presented) The device of claim 25 wherein the indexing spacer further comprises:

- a second connecting bolt;
- a pair of plates located on opposed sides of the finger gauges, the pair of plates attached to and pivoting about the first connecting bolt, the pair of plates having holes at one end to allow the second connecting bolt to pass therethrough; and
- a block located between the pair of plates at one end of the finger gauges, the block having a hole extending entirely through the block, the hole in the block holding the second connecting bolt whereby the block pivots about the second connecting bolt.